MONUMENT PRESERVATION/CORNER RECORD

- IF AT ANY TIME A SURVEY MONUMENT SET AT CENTERLINE OR PROPERTY CORNERS WILL BE DESTROYED, DISTURBED, OR COVERED MORE THAN 2" DURING CONSTRUCTION OR RE—PAVEMENT, THE SURVEY MONUMENT MUST BE PERPETUATED AND RESET IN ACCORDANCE TO THE CALIFORNIA LAND SURVEYOR'S ACT 8771 AND STATE CODES REGARDING SURVEY MONUMENTS.
- a. A PERMANENT MARKER SHALL BE RESET IN THE SURFACE OF THE NEW CONSTRUCTION, IN PLACE OF A WITNESS MONUMENT, OR MONUMENTS SET TO PERPETUATE THE LOCATION OF ANY MONUMENT THAT COULD BE DESTROYED, DAMAGED, COVERED, DISTURBED, OR OBLITERATED.
- b. THE MONUMENT TYPE SHALL BE DETERMINED BY THE CITY ENGINEER. REFER TO CITY STANDARD 6102-6105 FOR MONUMENT TYPES.
- c. ALL MONUMENTS SHALL BE LEFT UNCOVERED OR FLAGGED FOR FINAL INSPECTION.
- IT IS THE CONTRACTORS RESPONSIBILITY TO HIRE A PROFESSIONAL LAND SURVEYOR OR REGISTERED CIVIL ENGINEER LICENSED TO PRACTICE LAND SURVEYING.
- 3. A CORNER RECORD OR RECORD OF SURVEY SHALL BE GENERATED USING CITY STANDARDS 6100 SERIES AND DRAWN USING THE CURRENT PRESCRIBED CORNER RECORD FORM (BPC.8733.1) AND FILED WITH THE COUNTY SURVEYOR PRIOR TO THE RECORDING OF A CERTIFICATE OF COMPLETION FOR THE PROJECT.
- a. EACH CORNER RECORD SHALL INCLUDE THE NOTATION "CENTERLINE MONUMENT TIE OR PROPERTY CORNER DOCUMENTATION FOR (A COMPLETE REFERENCE TO THE PARCEL OR TRACT MAP)".
- b. PRIOR TO SUBMITTING A COPY TO THE COUNTY SURVEYOR, A PRE-RECORDED COPY OF THE CORNER RECORD OR RECORD OF SURVEY WILL NEED TO BE SUBMITTED TO THE ENGINEERING DEPARTMENT FOR REVIEW.



CITY OF ONTARIO

MONUMENT PRESERVATION

STANDARD DRAWING NUMBER

6111